



Exceeding The Limits To Always Get The Best

FEEL



AVADHISH
CERAMICS

1200x1600MM

CONNECTING THE VALUE OF SLAB



FEEL



CONTINUA+ LAMGEA **SYSTEM 5**
Lamina

CONTINUA+ is the most efficient, highest-productivity technology for the accurately managed manufacture of ceramic slabs and tiles, also producible with traditional bodies. The slabs are, in fact, formed without using a traditional press or mould, ensuring maximum flexibility in terms of size and thickness.



CONTINUA+ seamlessly integrates the powder forming phase and subsequent digital decoration. The key strengths of this exclusive process are high quality texturing and unrivalled surface shine.

PRODUCT Formats



The thicknesses are one of the most important elements characterizing.

15 mm is set aside for the most demanding product applications such as kitchen countertops.

Black



Grey



Ivory



White




Our collections offer professional-grade performance while seamlessly blending the latest innovations with a premium design aesthetic that is crafted with authentic, high-quality materials.

The Functionality of
The Residential Kitchen

Elevating Classic Style
for Today's Homeowner

Leading Edge Design
and Innovation

PRODUCT |
Range



PRODUCT |
Finishes

FEEL

A matte finish with a light layer of enamel for subtle shine and a pleasantly soft touch. Surface finish which is easy to clean.



APPLICATION Areas

AIRPORT



DISCOTHEQUES



INDUSTRIES



GYMNASIUMS



HOTELS



CORRIDORS HALLS



SCHOOLS



SUPER MARKET



OFFICE



TECHNICAL Features

LIGHTWEIGHT



WATERPROOF



RESISTANT TO SCRATCHES



RESISTANT TO HIGH
TEMPERATURES



EASY TO CLEAN



RESISTANT TO BENDING



100% NATURAL



RECYCLABLE





HYGIENIC



RESISTANT TO UV RAYS





MARQUINA FEEL

Random Face 3

BODY
BLACK BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



METAL BLACK

Random Face 3

BODY
BLACK BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



OPERA BLACK

Random Face 3

BODY
BLACK BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



PORTE NOIR

Random Face 3




BODY
BLACK BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



STONE BLACK

Random Face 3

BODY
BLACK BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



ACRON GREY FEEL

Random Face 3

BODY
GREY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



ATLANTIC GREY

Random Face 3

BODY
GREY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



CEMENTO FEEL

Random Face 3

BODY
GREY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



SANDSTONE

Random Face 3

BODY
GREY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



SPIDER GREY

Random Face 3

BODY
GREY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



STONE GREY

Random Face 3

BODY
GREY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



TRAVENTINO GREY FEEL

Random Face 3

BODY
GREY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



WILLIAM GREY FEEL

Random Face 3

BODY
GREY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



ACRON BEIGE FEEL

Random Face 3

BODY
IVORY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



BASALTOBEIGE

Random Face 4

BODY
IVORY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



CLOUD CREAM FEEL

Random Face 3

BODY
IVORY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



DOVE CREAM

Random Face 3


BODY
IVORY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



LIME STONE

Random Face 2

BODY
IVORY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



STONE MITICA

Random Face 3

BODY
IVORY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL





TERRAZZO BEIGE

Random Face 3

BODY
IVORY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



TRAVENTINO ROYAL FEEL

Random Face 3


BODY
IVORY BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



BORGHINI ORO

Random Face 3

BODY
WHITE BODY

FINISH
MATT

SIZE
1200x1600 MM



THICKNESS
15 MM

FEEL



COTTON WHITE STONE

Random Face 3



BODY
WHITE BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



EMPERIO WHITE

Random Face 3



BODY
WHITE BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



HEROZIN WHITE

Random Face 3

BODY
WHITE BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL



LUNA WHITE

Random Face 3

BODY
WHITE BODY

FINISH
MATT

SIZE
1200x1600 MM

THICKNESS
15 MM

FEEL

Cleaning & Maintenance

Our products are non porous (due to their high quality raw materials, stringent production parameters and state of the art technology), hence any dust or deposited waste cannot penetrate the surface.

For most cases only a damp cloth is sufficient for cleaning.

Regular cleaning highlights the aesthetic features of the surface and gives it exceptional shine.

For highly aggressive cleaning caused by some common food and substances follow the table below.

TYPE OF STAIN	CHEMICAL PRODUCT	EXAMPLE
Grease	Alkaline - Solvent	Detergent
Oil	Solvent	Ammonia, Backing Soda
Ink	Oxidant - Solvent	Alcohol, Liquid Bleach, Nail Paint Remover
Rust	Acid	Hydrochloric Acid, Vinegar, Red Harpic
Lime	Acid	Descaling Reagent, Hydro Chloric Acid
Cement	Acid	Hydro Chloric Acid
Wine	Alkaline	Ammonia, Liquid Bleach
Coffee	Alkaline - Solvent	Ammonia, Liquid Bleach
Rubber	Solvent	Alcohol, Thinner
Plaster	Acid	Hydro Chloric Acid
Candle Wax	Solvent	Alcohol, Thinner
Iodine	Oxidant	Liquid Bleach
Blood	Oxidant	Liquid Bleach
Ice Cream	Alkaline	Liquid Bleach

Note: It is recommended that any kind of stain needs to get clean immediately / as soon as possible.

Technical Specification

CHARACTERISTIC	STANDARD AS PER ISO13006-2018/ EN14411 Gr.Bla	MEAN VALUE	TEST METHOD
Regulatory Properties			
Deviation in Length and Width	± 0.30 % (±1.00mm)	± 0.10 %	ISO 10545-2
Deviation in Thickness	± 5.00 % (±0.50mm)	± 5.00 %	ISO 10545-2
Straightness in Side	± 0.30 % (±0.80mm)	± 0.10 %	ISO 10545-2
Rectangularity	± 0.30 % (±1.50mm)	± 0.10 %	ISO 10545-2
Surface Flatness Central Curvature	± 0.40 % (±1.80mm)	± 0.50 %	ISO 10545-2
Surface Flatness Edge Curvature	± 0.40 % (±1.80mm)	± 0.50 %	ISO 10545-2
Surface Flatness Warpage	± 0.40 % (±1.80mm)	± 0.50 %	ISO 10545-2
Surface Quality	> 95% defects free	> 95% defects free	ISO 10545-2
Small Color Difference(for Plain Colour)	ΔE < 1.00	ΔE < 0.30	ISO 10545-16
Glossiness (Polished)	as per mfg.	Gloss Value> 90	Gloss Meter 60°
Glossiness (Matt)	as per mfg.	3 <Gloss Value<7	Gloss Meter 60°
Glossiness (Satin/Posh)	as per mfg.	7<Gloss Value<18	Gloss Meter 60°
Structural Properties			
Water absorption	≤ 0.50 %	≤ 0.060 %	ISO 10545-3
Bulk density	as per mfg.	Min. 2.28 g/cc	ISO 10545-3
Massive Mechanical Properties			
Modulus of rupture	Min. 35.0 N/mm ²	Min. 42.0 N/mm ²	ISO 10545-4
Breaking strength thickness <7.5	Min. 700.0 N	Min. 1000.0 N	ISO 10545-4
Breaking strength thickness ≥7.5	Min. 1300.0 N	Min. 1800.0 N	ISO 10545-4
Breaking strength thickness ≥7.5mm	Min. 1300.0 N	Min. 7500.0 N	ISO 10545-4
Surface Mechanical Properties			
MOH'S hardness #	as per mfg.	Glossy Min. 4 / Posh Min. 6	BS EN 15771
Surface abrasion resistance #	as per mfg.	Glossy Min. 2 / Posh Min. 3	ISO 10545-7
Deep abrasion resistance #	Max. 175mmh	Max. 132mmh	ISO 10545-6
Thermal Hydrometric Properties			
Moisture expansion	Max. 0.06%(0.6mm/m)	Max. 0.02mm/m	ISO 10545-10
Thermal expansion(COE) at 100°C	as per mfg.	Max. 6.0 x 10 ⁻⁶	ISO 10545-8
Thermal shock resistance	Min. 10 Cycle	Min. 10 Cycle	ISO 10545-9
Impact resistance(COR) #	Min. 0.55	Min. 0.55	ISO 10545-5
Frost resistance	as per mfg.	Frost Proof	ISO 10545-12
Chemical Properties			
Resistance to staining glazed	Min. Class 3	Min. Class 4	ISO 10545-14
Resistance to household chemicals & swimming pool salts glazed	Min. Class GB	Min. Class GA	ISO 10545-13
Resistance to low concentrate acid and alkalis glazed	as per mfg.	Min. Class GLB**	ISO 10545-13
Resistance to high concentrate acid and alkalis glazed	as per mfg.	Min. Class GHB**	ISO 10545-13
Safety Properties			
Skid resistance(DCOF-DRY) ##	as per mfg.	Glossy P0(¹) / Posh ≥P1 ⁽²⁻⁴⁾	BS 7976-2
Slip resistance(DCOF)(R value) ##	as per mfg.	R9 to R11	DIN 51130
Fire resistance	as per mfg.	Fire Proof	N.A.

* With Nano polished
 ** Except Hydrofluoric Acid & its compound
 # Tiles Intended for use on floor
 ## As per customer requirement

Packing Details

PRODUCT	BODY	SIZE	THICKNESS	TILES / BOX	COVERAGE AREA / BOX	WEIGHT (Kg)
Matt	Color Body	1200x1600mm	15mm	1pc	20.67 Sq ft	67 Kgs